

7720ULFPLUS

COMBINATION FIRE CONTROL AND
LONG RANGE RADIO TRANSMITTER



Honeywell's 7720ULFPLUS Combination Fire Control and Long Range Radio Transmitter is UL listed for property protection and life safety. It provides fire compliance at a cost less than systems requiring two separate telephone lines.

All signals are delivered to the AlarmNet Control Center, which routes the information to the appropriate central station.

The AlarmNet Control Center is fully redundant and monitored 24 hours a day, seven days a week. AlarmNet has the ability to route messages using the AlarmNet-A, AlarmNet-M, AlarmNet-i and 800 plus networks; all of which provide true redundancy and the highest reliability in message delivery.

FEATURES

- Utilizes AlarmNet-A service
- UL, FM, MEA, CFM listed
- Allows direct connection to waterflow detectors, pull stations and supervisory switches
- Housed in red metal cabinet with key lock
- Eight programmable zones – 2 Class A, 6 Class B
- Programmable delays for supervisory and waterflow applications
- Voltage trigger or dry contact input
- Built-in annunciation
- Bell supervision
- Ground fault supervision
- Trouble buzzer with manual reset and latching trouble LED on board

SPECIFICATIONS

Electrical

- Voltage input: 18VAC, 40VA
- Current drain: 100mA standby; 900mA alarm
- Trigger input: 3.7 to 14 Volts into 2k Ohms

Mechanical

- Dimensions: 4" W x 12" H x 12" D
- Operating temperature: 32° to 122° F (0° to 50°)

UL/CUL Listings

- UL listed for Commercial Fire – UL864
- CSFM • FM • MEA

AlarmNet Services

- A** AlarmNet-A Original AlarmNet
- M** AlarmNet-M Mobitex System
- C** AlarmNet-C Control Channel Cellular
- I** AlarmNet-i Internet

Ask your provider for the AlarmNet technology used in your area.

7720ULFPLUS

COMBINATION FIRE CONTROL AND LONG RANGE RADIO TRANSMITTER

ACCESSORIES

7720P
Programming Tool



7626-5, 7626-12, 7626-25HC, 7626-50HC
Low Loss Coax Cables



7715DF
Installation Tool



7625-3dB
Omni Directional Antenna (3dB)



7674
Directional Antenna (6dB)



7825
Weatherproof Outdoor Antenna



7670F*
Remote Application with 7625-3 Antenna



7620**
Transformer



Recommended Smoke Detectors

Model	Description
4W-B	i3 Series four-wire standard detector
4WT-B	i3 Series four-wire standard detector with thermal
4WTA-B	i3 Series four-wire standard detector with sounder and thermal

Model	Description
4WTR-B	i3 Series four-wire standard detector with Form C relay and thermal
4WTAR-B	i3 Series four-wire standard detector with sounder, Form C relay and thermal
4WITAR-B	i3 Series four-wire standard detector with sounder, Form C relay and isolated thermal

*The 7670F Antenna Bracket is required when remoting 7625-3dB Antenna. (Accessory cable required.)

ORDERING

7720ULFPLUS Synthesized Combination Fire Control and Long Range Radio

7720ULFKT **7720ULFPLUS**, **7625-3dB** Antenna, **7620TR** Transformer and **712BNP** Battery

7720ULFKT-EX **7720ULFPLUS**, **7625-3dB** Antenna, **7620TR** Transformer, **712BNP** Battery, **7670F** Antenna Bracket and **7626-25HC** Cable

Honeywell Security & Custom Electronics
Honeywell International Inc.
PO Box 9035
Syosset, NY 11791
www.honeywell.com

AL06011
L/7720ULF/D
April 2006
©2006 Honeywell International, Inc.

Honeywell